ME260

SMART RESIDENTIAL METER.



Iskraemeco's next generation smart meters are deployed for the smart residential consumer/prosumer. The best-in-class design, cost-efficient, reliable and secure communication and the intelligent 'Measure Everything' innovative platform, enables a seamless integration of smart metering functions into the smart grid and assures maximum flexibility.



FEATURES

- Future proof platform.
- Last Gasp and First Breath.
- Universal standardized transparent passthrough communication interface.
- Communication according to IS 15959 -1 and IS 15959 - 2
- Extended set of embedded Smart Grid functions.
- Compliance with IS 16444.
- Support of both prepayment and post payment mode.
- Extended load profile and maximum demand measurement.

- Front mounted communications module for easy access.
- Solid anti-tamper features.
- Four quadrant metering with import/export registration.
- ESD compliance at factory.
- Passes through highest reliability standard with HALT/ALT and HASS.

KEY BENEFITS

- Modular communication to support different WAN/NAN modules (RF, 2G/3G/4G, NBIoT).
- Integrated high-level security mechanism.
- Remote firmware upgradeability of meter.
- Push alarms for real-time monitoring and intervention.

			ME260
TECHNICAL SPECIFICATIONS			
Network			Low voltage
Connection type			1P2W
Communication			Local - Optical port
Nominal voltage Un			240 V, -40% to +20%
Voltage range			0.8 - 1.15 Un
Current	Base current	lb	5, 10 A
	Maximal current	lmax	60, 100 A
Accuracy class			Active Class 1 (IS 16444), Reactive class 2
Temperature range	Operation		-10 °C to +60 °C
	Storage		-25 °C to 70 °C
Ingress protection			IP51